

501 200

10 METERS MAXIMUM HOSE CAPACITY

**Full metal hose reels, can handle up to 10 m x 1/2" hose.**

**FLUIDS HANDLED**


- Air.
- Water.
- Antifreeze Solutions.
- Synthetic and Mineral Oils.
- Grease.

**MARKETS / APPLICATIONS**

- Car and truck dealers.
- Service shops.
- General manufacturing.
- Service stations.
- Quick lubes.

**MOUNTING**

- Floor.
- Wall.
- Ceiling.
- Tank.



Dimensions mm (inches)

- Fatigue resistant steel spring for years of durable performance and even load when pulling and recoiling the hose.
- Full metal double pedestal arm construction, epoxy powder coated for increased wear resistance.
- Forged brass shaft ensures a leak free operation.
- Hose reels with hose include 0.8 m inlet hose.



Reel with arms in ceiling mounting position.

PART No.	BARE REEL	HOSE IN Ø	HOSE LENGTH	CONNECTING HOSE INLET	DELIVERY HOSE OUTLET	PRESSURE RATING	WEIGHT (With hose)
<b>AIR - WATER - ANTIFREEZE SOLUTIONS</b>							
<b>501 100</b>	<b>501 198</b>	3/8"	10 m	1/2" BSP (M)	1/4" BSPT (M)	20 bar	17.9 kg
<b>MINERAL AND SYNTHETIC LUBRICANTS</b>							
<b>501 200</b>	<b>501 298</b>	1/2"	10 m	1/2" BSP (M)	1/2" BSP (M)	160 bar	20 kg
<b>GREASE</b>							
<b>501 300</b>	<b>501 398</b>	1/4"	10 m	1/2" BSP (M)	1/4" BSP (M)	400 bar	19.2 kg

(1) Bare reels include hose stopper and adaptors for connecting flow delivery and inlet hoses.